BS62-4Ab/28

4-stroke Rammers

Outstanding work performance and long service life

Wacker Neuson's 4 stroke rammers characterized by excellent work performance. The long shoe stroke, the high ramming frequency, high impact energy and fast travel speed ensure first-class work results. Well thought-out functions make the use of the 4 stroke rammers even more operator-friendly, extend their service life, and minimize maintenance.

Highlights

- Large stroke, high impact force
- Just one lever for starting, idling and stopping
- Efficient air filter
- Ergonomic guide handle
- Low oil warning indicator
- Large stroke, high impact force
- Efficient air filter
- Ergonomic guide handle

Technical Data

Mechanical - Output Details

Number of blows	689.0 1/min
Area capacity	2,174.3 ft2/h
Forward Running	0.7 fps
Power of impact	3,821.8 lbf

Mechanical Details

Length	26.1 "
Length Ramming Shoe	13.4 "
Width	13.7 "
Width Ramming Shoe	11.0 "
Height	36.2 "
Weight	139.55 lb
Operating weight	141.1 lb
Stroke at tamper	2.7 "

Environment Data

Operating temperature range	14 - 104 °F
Sound power LWA, guaranteed	108.0 dB(A)
Sound power LWA (Standard)	EN 500-4
HAV summation (average value)	32.8 ft/s2
HAV summation (Standard)	EN 500-4

Electrical System

Display Equipment	Beacon
Operating elements	Pushbutton OFF

Operating Fluids

Oil specification	SAE 10W-40
Oil volume	0.185 gal US

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2024 Wacker Neuson SE | www.wackerneuson.com